



SURU INTERNATIONAL PVT. LTD.



GUIDEWIRES

Product Name: Guidewires

Item Code: Item Code # 4124

Features :

- Made from kink resistance SS 304 OR Nitinol core
- Available with floppy “Straight” or “J” Tip to prevent vessel damage
- Uniform coating of PTFE provides lubricity and a smooth outer surface for easy insertion
- Tight specifications provide accurate measurements for improved catheter tracking
- Guidewire transmit rotational forces from the operator’s hand to the tip
- Permits shape memory retention of the distal tip throughout process
- Available in wide range of diameters from 0.018” to 0.035”
- Individually packaged, sterile and for single use

Option Available :

- Hydrophilic PTFE Coated
- Straight or J tip
- Stainless Steel or Nitinol

Available Configuration :

Sr. No	O.D	Length	J/ Straight Tip	Core wire	Coating type
1	0.032”, 0.035, 0.038	50 -80 cm	J/ ST	S. S. 304	Uncoated
2	0.032”, 0.035, 0.038	50 cm	J/ ST	Nitinol	Uncoated
3	0.032”, 0.035, 0.038	60 cm	J/ ST	Nitinol	Uncoated
4	0.032”, 0.035, 0.038	70 cm	J/ ST	Nitinol	Uncoated
5	0.032”, 0.035, 0.038	150 cm	J/ ST	S. S. 304	Uncoated
6	0.032”, 0.035, 0.038	260 cm	J/ ST	S. S. 304	Uncoated
7	0.032”, 0.035,	150 cm	J/ ST	S. S. 304	PTFE

	0.038				coated
8	0.032", 0.035, 0.038	260 cm	J/ ST	S. S. 304	PTFE coated
1	0.025", 0.028"	50 cm	J/ ST	Nitinol	Uncoated
2	0.025", 0.028"	60 cm	J/ ST	Nitinol	Uncoated
3	0.025", 0.028"	70 cm	J/ ST	Nitinol	Uncoated
6	0.025", 0.028"	150 cm	J/ ST	S. S. 304	PTFE coated
7	0.025", 0.028"	260 cm	J/ ST	S. S. 304	PTFE coated
1	0.018, 0.021	50 cm	J/ ST	Nitinol	Uncoated
2	0.018, 0.021	60-70 cm	J/ ST	Nitinol	Uncoated
3	0.018, 0.021	50 cm	J/ ST	S. S. 304	Uncoated
4	0.018, 0.021	60-70 cm	J/ ST	S. S. 304	Uncoated
5	0.018, 0.021	150 cm	J/ ST	S. S. 304	Uncoated
6	0.018, 0.021	150 cm	J/ST	S. S. 304	PTFE coated

<http://www.suru.com/Central-Venous-Access-/-Dialysis/Guidewires-1>